

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



Part #: VP7541

Model Number: XPB240-103IJ4TL6

Category: Basic

Sub Category: Standard

Power Configuration: 30A, 208V, 4.9kW

Physical Configuration: 66in / 1683mm, Vertical

Product Summary: rPDU, Basic Standard, 30A, 208V, 4.9kW, Vertical, (20) IEC C13, (4) IEC C19, 10ft power cord with L6-30P, Black Powder Coat.

Plug Form:



L6-30P

Receptacle:



IEC C13
(Quantity: 20)



IEC C19
(Quantity: 4)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

| | |
|------------------------------|--------------|
| Quantity Of Inputs | 1 |
| Voltage | 200-240V |
| Current | 30A |
| VA per Input (Load Capacity) | 4.9kW (208V) |

| | |
|---|---|
| Frequency | 50/60Hz |
| Over Current Protection | (2) 20A Double Pole Magnetic Breakers |
| Switch | Breaker/Switch Combination |
| Power Cable Wire Gauge | 10/3 |
| Power Cable Length | 10ft |
| Plug Type | NEMA L6-30P Twistlock |
| Combined Total Receptacle/Socket Quantity | 24 |
| Receptacle/Socket Type #1 | IEC C13 |
| - Quantity on Face | 20 |
| - Quantity per Breaker | 10 |
| - Style | Banks of 5 |
| - Maximum Output per Receptacle/Socket | 15A per receptacle bank |
| - Voltage per Receptacle/Socket | 208V |
| Receptacle/Socket Type #2 | IEC C19 |
| - Quantity on Face | 4 |
| - Quantity per Breaker | 2 |
| - Style | Individual |
| - Maximum Output per Receptacle/Socket | 20A |
| - Voltage per Receptacle/Socket | 208V |
| Continuous Operating Temperature Range | 10-45C / 50-113F |
| Heavy Steel - Powder Coat Finish | Black |
| Configuration | 66in / 1683mm Vertical Rackmount |
| 7938 Vertical Mounting Bracket Kit | Yes |
| Toolless Mounting Hardware - Center to Center Spacing | 61.25in and 64.75in |
| Country of Origin | USA, TAA Compliant and Buy American Act COTS Compliant |
| Product Warranty | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals | RoHS Compliant |
| Certification/Agency Approvals | UL & c-UL Listed 60950 |
| Chassis Dimensions (LxWxD) | 66.25in x 2.0in x 2.0in |
| Doghouse (D) | 1.44in |
| Shipped Weight | 17lbs (7.71kg) |