

## OVERVIEW

Upgradeable Switched Outlet Level Monitored rPDUs provide reliable power distribution to critical IT equipment while delivering individual outlet level control and a comprehensive view of outlet level power usage via remote network access. Includes environmental monitoring capabilities to obtain real-time environmental metrics. With the PowerIT Upgradeable hot-swap technology, users may easily update the rPDU technology with the addition of the appropriate Interchangeable Monitoring Device (IMD) as business needs change.

### Benefits

- Remotely reboot outlets to power cycle unresponsive IT equipment or increase runtime of critical equipment upon power failure with outlet-level control.
- Reliable power distribution with local and remote outlet-level power monitoring options offer quick access to critical power usage information down to the device level to evaluate energy usage trends and maximize uptime.
- Environmental monitoring capabilities with the addition of optional environmental sensors ensure users have critical infrastructure data at their fingertips to prevent climate-related equipment failure and system downtime.
- Fault-Tolerant Daisy Chaining with RSTP simplifies intelligent rPDU connectivity and ensures data is reported even when a break in the network chain occurs. Supports up to 40 rPDUs.



## Part #: VP7P30A3

**Model Number:** MPU5MGW1-36PT68-3JL15A5A10-S-A

**Category:** Switched

**Sub Category:** Outlet Level Monitoring

**Power Configuration:** 30A, 200V DELTA, 10.3kW

**Physical Configuration:** 72in / 1829mm, Vertical

### Product Summary:

rPDU, Switched Outlet Level Monitoring EC, 30A, 200V Delta, 10.3kW, Vertical, (30) Locking IEC C13, (6) Locking IEC C19, 10ft / 3m power cord with L15-30P, Black Powder Coat.

### Monitoring:

Input and Outlet power monitoring with Outlet switching. Circuit/Breaker current monitoring. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility display.

### Plug Form:



L15-30P

### Receptacle:



Locking IEC C13  
(Quantity: 30)



Locking IEC C19  
(Quantity: 6)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

- Daisy-chain up to 50 devices on a single IP address and reduce deployment time with self-configuration of downstream devices.

|   |  |
|---|--|
| <b>Monitoring</b>                                   | Input and Outlet power monitoring with Outlet switching. Circuit/Breaker current monitoring. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility display. |
| <b>Input Monitoring</b>                             | Total Unit Monitoring (kWh, W, VA, PF)<br>Phase (A, B, C) Monitoring (kWh, W, VA, PF, V, A)<br><br>Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements                   |
| <b>Circuit Monitoring</b>                           | Circuit / Breaker Monitoring (A)<br><br>Circuit/Breaker Current Measurements Independently Tested and Verified at 1% Accuracy  |
| <b>Outlet Monitoring</b>                            | Outlet Monitoring (kWh, W, VA, PF, V, A)<br><br>Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements.   |
| <b>Remote Power Management</b>                      | Individual Outlet Switching with Optional User Defined Time Delays and Sequential Power-up   |
| <b>Quantity Of Inputs</b>                           | 1  |
| <b>Voltage</b>                                      | 200-240V Delta   |
| <b>Current</b>                                      | 30A x 3 Phase DELTA  |
| <b>VA per Input (Load Capacity)</b>                 | 10.3kW (200V)  |
| <b>Frequency</b>                                    | 50/60Hz  |
| <b>Over Current Protection</b>                      | (3) 20A Double Pole Magnetic Breakers (10kAIC Rated)   |
| <b>Switch</b>                                       | Breaker/Switch Combination   |
| <b>LCD Touchscreen Display / Auto Oriented</b>      | Yes  |
| <b>Indicators - LED(s)</b>                          | 36   |
| <b>Power Cable Wire Gauge</b>                       | 5.5mm <sup>2</sup>   |
| <b>Power Cable Length</b>                           | 10ft / 3m  |
| <b>Power Entry Location</b>                         | Bottom Front   |
| <b>Plug Type</b>                                    | NEMA L15-30P Twistlock   |
| <b>Combined Total Receptacle/Socket Quantity</b>    | 36   |
| <b>Alternating Phase/Circuits</b>                   | Yes  |
| <b>Receptacle/Socket Type #1</b>                    | U-Lock IEC C13   |
| <b>- Quantity on Face</b>                           | 30   |
| <b>- Quantity per Breaker and Phase Combination</b> | 10   |
| <b>- U-Lock Color ID</b>                            | 3 Circuit = Orange, Green, Blue  |
| <b>- Style</b>                                      | Individual   |
| <b>- Voltage per Receptacle/Socket</b>              | 200V   |
| <b>Receptacle/Socket Type #2</b>                    | U-Lock IEC C19   |
| <b>- Quantity on Face</b>                           | 6  |
| <b>- Quantity per Breaker and Phase Combination</b> | 2  |
| <b>- U-Lock Color ID</b>                            | 3 Circuit = Orange, Green, Blue  |
| <b>- Style</b>                                      | Individual   |
| <b>- Voltage per Receptacle/Socket</b>              | 200V   |
| <b>Network Connection</b>                           | Dual 10/100/1000Mbps Ethernet  |

|  |  |
|--|--|
| <b>Protocols Supported</b>                                   | DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+, Modbus TCP |
| <b>Data Access Formats</b>                                   | CSV datalog, JSON API, JSON datalog  |
| <b>USB Support</b>   | Yes  |
| <b>IP Reset Button</b>                                       | Yes  |
| <b>Hard Reboot Button</b>                                    | Yes  |
| <b>Serial Connection</b>                                     | RS232 via RJ45   |
| <b>Remote Sensor RJ Connection Jacks</b>                     | 1 (Supports up to 16 Sensors)  |
| <b>Maximum Operating Temperature</b>                         | 60C / 140F   |
| <b>Heavy Steel - Powder Coat Finish</b>                      | Black  |
| <b>Configuration</b>   | Zero U   |
| <b>Toolless Mounting Hardware - Center to Center Spacing</b> | 61.25in and 64.75in / 1556mm and 1645mm  |
| <b>Country of Origin</b>                                     | USA, TAA Compliant and Buy American Act COTS Compliant   |
| <b>Product Warranty</b>                                      | 5-year limited warranty  |
| <b>Certification/Agency Approvals</b>                        | RoHS Compliant   |
| <b>Certification/Agency Approvals</b>                        | METI DENAN   |
| <b>Chassis Dimensions (LxWxD)</b>                            | 72in x 2in x 2.6in / 1829mm x 51mm x 66mm  |
| <b>Doghouse (D)</b>  | 1.4in / 36mm   |
| <b>Shipped Weight</b>  | 22lbs (9.98kg)   |