

## OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

### Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.



## Part #: VP9562

**Model Number:** BRN100-10

**Category:** Basic

**Sub Category:** Standard

**Power Configuration:** 15A, 120V, 1.4kW

**Physical Configuration:** 19in / 483mm, Horizontal

**Product Summary:** rPDU, Basic Standard, 15A, 120V, 1.4kW, Horizontal, (10) NEMA 5-15R, 10ft power cord with 5-15P, Black Powder Coat.

### Plug Form:



5-15P

### Receptacle:



NEMA 5-15R  
(Quantity: 10)

### Chassis Color Options:



To discuss color options, contact your local sales representative.

## Product Specification and Options

### System Features

|                              |              |
|------------------------------|--------------|
| Quantity Of Inputs           | 1            |
| Voltage                      | 100-120V     |
| Current                      | 15A          |
| VA per Input (Load Capacity) | 1.4kW (120V) |
| Frequency                    | 50/60Hz      |

|   |   |
|---|---|
| <b>Over Current Protection</b>                | 15A Thermal Breaker   |
| <b>Switch</b>                                 | No  |
| <b>Indicators - LED(s)</b>                    | 1 - Power ON Green LED  |
| <b>Power Cable Wire Gauge</b>                 | 14/3  |
| <b>Power Cable Length</b>                     | 10ft  |
| <b>Plug Type</b>                              | NEMA 5-15P  |
| <b>Receptacle/Socket Type #1</b>              | NEMA 5-15R  |
| <b>- Quantity on Rear</b>                     | 10  |
| <b>- Quantity per Breaker</b>                 | 10  |
| <b>- Style</b>                                | Duplex  |
| <b>- Maximum Output per Receptacle/Socket</b> | 15A   |
| <b>- Voltage per Receptacle/Socket</b>        | 120V  |
| <b>Continuous Operating Temperature Range</b> | 10-45C / 50-113F  |
| <b>Heavy Steel - Powder Coat Finish</b>       | Black   |
| <b>Configuration</b>                          | 19in / 483mm Horizontal Rackmount   |
| <b>Flush Mount</b>                            | Yes   |
| <b>Country of Origin</b>                      | USA, TAA Compliant and Buy American Act COTS Compliant  |
| <b>Product Warranty</b>                       | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| <b>Certification/Agency Approvals</b>         | RoHS Compliant  |
| <b>Certification/Agency Approvals</b>         | UL & c-UL Listed 60950  |
| <b>Chassis Dimensions (HxWxD)</b>             | 1.72in x 17in x 3.75in  |
| <b>Shipped Weight</b>                         | 6lbs (2.72kg)   |