

UPPER VIEW

FRONT VIEW

OUTPUT POWER

CIRCUIT	RECEPTACLE TYPE (QUANTITY)	VOLT AGE (V)	MAX. CONTINUOUS AMPS (A)	
			PER RECEPTACLE	PER CIRCUIT
1	6x Combination C13/C19	200-240	12/16	16
1	2x NEMA 5-20R	100-120	16	16
2	6x Combination C13/C19	200-240	12/16	16
2	2x NEMA 5-20R	100-120	16	16

INPUT POWER

INPUT CORD	INPUT SOCKET	WIRE COUNT	FREQUENCY (Hz)	VOLTAGE (V)	RATED AMPS (A)	MAX. CONT. AMPS (A)
10 FT	NEMA14-30P	2/N/PE	50/60	120/208V	30	24

METERING PARAMETER	MEASUREMENT ACCURACY
VOLTAGE	±1%
CURRENT	±1% - Input Current ±1% - Circuit/Breaker Current

AGENCY COMPLIANCE:

RoHS Compliant

FCC Part 15 Class A Conformance

UL & c-UL Listed 62368-1

ENVIRONMENTAL RATING:

Maximum Operating Temperature: 60C / 140F

NOTES


UNIT DIMENSIONS: 1.72in x 17in x 8.5in

SHIPPED WEIGHT: 15lbs

SHIPPING DIMENSIONS: 25in x 14in x 6in



L14-30P

 Dimensions in mm				Allgemeintoleranzen General tolerances CHASSIS(L,W,D) ± 0.8mm - CORD ± 3.2mm		Oberfläche Finish PAINT - BLACK WRINKLE POWDER		Werkstoff / Material 18 GAUGE SEEL OR METRIC EQUIVALENT -		Gewicht: - Weight:	
				Date	Name	Bezeichnung / Description rPDU, Basic, Standard, 30A, 120/208V, 5.7kW, Horizontal, (12) Combination C13/C19, (4) NEMA 5-20R, 10ft power cord with L14-30P, Black Powder Coat.					
				Drawn 10/30/2025	TBC						
				Checked -	-						
				Approved -	-	Zeichnungs-Nr. / Drawing no. VP0N3100 Verwendet in / Used in -					
				 VERTIV™							
-	-	-	-			Maßstab Scale 1:10					
Rev.	Change	Date	Name								Blatt/Sheet 1/1

Disclosure and photocopying of this document, exploitation and communication of its contents are not permitted, unless permission is expressly granted. All rights are reserved.

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mittelung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich zugestanden. Alle Rechte vorbehalten.