

4

3

2

1

D

D

C

C

B

B

A

A

REAR VIEW

69.1  
[2.72]

88.9  
[3.50]

1644.7  
[64.75]

#10-32 BLIND PEM NUT  
(REQUIRED FOR TOOLES MOUNTING)  
3 PLACES

SIDE VIEW

66.1  
[2.60]

1778.0  
[70.00]

50.8  
[2.00]

FRONT VIEW

### OUTPUT POWER

CIRCUIT	PHASE	RECEPTACLE TYPE (QUANTITY)	VOLTAGE (V)	MAX. CONTINUOUS AMPS (A)	
				PER RECEPTACLE	PER CIRCUIT
1	A	6xSDG400	277	16	16
2	B	6xSDG400	277	16	16
3	C	6xSDG400	277	16	16
4	A	6xSDG400	277	16	16
5	B	6xSDG400	277	16	16
6	C	6xSDG400	277	16	16

NEMA L22-30P



AGENCY COMPLIANCE:  
ETL & c-ETL Listed to UL 62368-1  
RoHS Compliant  
FCC Part 15 Class A Conformance

ENVIRONMENTAL RATING:  
Maximum Operating Temperature: 60C / 140F

NOTES  
UNIT DIMENSIONS: 72in x 2in x 2.6in / 1829mm x 51mm x 66mm  
SHIPPED WEIGHT: 30lbs (13.61kg)  
SHIPPING DIMENSIONS: 72in x 9in x 7in / 1829mm x 223mm x 159mm  
Toolless Mounting Hardware 61.25in / 1556mm and 64.75in / 1645mm

### INPUT POWER

INPUT CORD	INPUT PLUG	WIRE COUNT	FREQUENCY (Hz)	VOLTAGE (V)	RATED AMPS (A)	MAX. CONT. AMPS (A)
10ft	NEMA L22-30P	3/N/PE	50/60	277/480V WYE	30A	24A

METERING PARAMETER	MEASUREMENT ACCURACY
VOLTAGE	±1%
CURRENT	±1% - Input Current ±1% - Circuit/Breaker Current

VERTIV  
1777 YOLANDE AVENUE  
LINCOLN, NEBRASKA 68521

CORPORATE CAGE CODE 1EDC2	505 N. CLEVELAND AVE WESTERVILLE, OHIO 43082	VP1N30AT PART NUMBER	VP1N30AT-ASM DESCRIPTION
<small>© 2025 VERTIV GROUP CORP. CONFIDENTIAL AND PROPRIETARY. ALL RIGHTS RESERVED. VERTIV AND THE VERTIV LOGO ARE TRADEMARKS OR REGISTERED TRADEMARKS OF VERTIV GROUP CORP. THIS DOCUMENT (AND THE INFORMATION IT CONTAINS) ARE THE PROPERTY OF VERTIV GROUP CORP. BY ACCEPTING IT INTO YOUR POSSESSION, YOU AGREE THAT YOU WILL KEEP THIS DOCUMENT AND ALL INFORMATION CONTAINED HEREIN IN STRICTEST CONFIDENCE AND WILL NOT COPY, RETRANSMIT USE (EXCEPT SOLELY FOR THE BENEFIT OF VERTIV GROUP CORP.), SELL, LEND, OR OTHERWISE DISPOSE OF SAME, DIRECTLY OR INDIRECTLY, WITHOUT THE EXPRESS WRITTEN PERMISSION OF VERTIV GROUP CORP., AND THIS DOCUMENT SHALL BE RETURNED TO VERTIV GROUP CORP. IMMEDIATELY UPON REQUEST.</small>			
MATERIAL: N/A		UNLESS OTHERWISE SPECIFIED TOLERANCE: MM (PRIMARY) INCHES (SECONDARY) X ±.25 (X) ±.1 XX ±.75 (XX) ±.03 XXX ±.25 (XXX) ±.01 HOLE DIA +.08 HOLE DIA +.003 ANGULAR ±2°	
DESIGNED BY: JEFF MICEK	DATE: 2026-02-12	WEIGHT: -	CONTROL CHARACTERISTICS THIRD ANGLE PROJECTION SIZE B SCALE 1:6
DRAWN BY: JEFF MICEK	DATE: 2026-02-12	SHEET: 1/1	
PART DESCRIPTION VP1N30AT-ASM		DOCUMENT NUMBER VP1N30AT	

4

3

2

1