



E	3	12x Combination C-13/C-19	200-240	12/16	16
---	---	---------------------------	---------	-------	----

F	CURRENT	±1% - Input Current ±2% - Circuit/Breaker Current		-	-	-	-		1.5
---	---------	--	---	---	---	---	---	---	-----


1	2	3	4			
---	---	---	---	--	--	--



RoHS Compliant
FCC Part 15 Class A Conformance
UL & c-UL Listed 62368-1

Maximum Operating Temperature: 60C/140F

UNIT DIMENSIONS: 70in x 2in x 2in / 1778mm x 51mm x 51mm
SHIPPED WEIGHT: 17lbs (7.71kg)
Mounting Hardware: 7938 Vertical Mounting Bracket Kit; Toolless Mounting Hardware - Center to Center
Spacing: 61.25in and 64.75in

 Dimensions in mm				Allgemeintoleranzen General tolerances CHASSIS (L,W,D) ±0.8mm CORD – ±3.2mm		Oberfläche Finish BLACK PAINT – WRINKLE POWDER		Werkstoff / Material 18 GAUGE STEEL OR METRIC EQUIVALENT –		Gewicht: – Weight:	
					Date	Name	Bezeichnung / Description rPDU, Monitored Unit Level EC, 30A, 208V DELTA, 8.6kW, Vertical, (36) Combination C13/C19, 10ft power cord with L15-30P, Black Powder Coat				
Drawn	1/7/2025	CA									
Checked	–	–									
Approved	–	–									
				 VERTIV™				Zeichnungs-Nr. / Drawing no. VP4N30AJ		Maßstab Scale 1:5	
								Verwendet in / Used in –		Blatt/Sheet 1/1	
Rev.	Change	Date	Name								