



RoHS Compliant
FCC Part 15 Class A Conformance
UL & c-UL Listed 62368-1


Maximum Operating Temperature: 60C/140F

UNIT DIMENSIONS: 70in x 2in x 2.25in / 1778mm x 51mm x 58mm
SHIPPED WEIGHT: 19lbs (8.62kg)
Mounting Hardware: 7938 Vertical Mounting Bracket Kit;
Toolless Mounting Hardware - Center to Center Spacing: 61.25in and 64.75in
IEC60309 3P + N + E, 30A, Splashproof IP44⁴

INPUT POWER						
INPUT CORD	INPUT PLUG	WIRE COUNT	FREQUENCY (Hz)	VOLTAGE (V)	RATED AMPS (A)	MAX. CONT. AMPS (A)
10ft/3m	IEC60309 3P + N + E, 30A, Splashproof IP44	3/N/PE	50/60	200-240/346-415V	30A	24A

METERING PARAMETER	MEASUREMENT ACCURACY
VOLTAGE	±1%
CURRENT	±1% - Input Current ±2% - Circuit/Breaker Current



 Dimensions in mm				Allgemeintoleranzen General tolerances CHASSIS (L,W,D) ±0.8mm CORD ±3.2mm		Oberfläche Finish BLACK PAINT – WRINKLE POWDER		Werkstoff / Material 18 GAUGE STEEL OR METRIC EQUIVALENT –		Gewicht: – Weight:		
					Date	Name	Bezeichnung / Description					
				Drawn	12/19/2024	CA	rPDU, Monitored Unit Level EC, 30A, 240/415V WYE, 17.2kW,Vertical, (36) Combination C13/C19, 10ft power cord with3P+N+E (IP44), Black Powder Coat.					
				Checked	-	-						
				Approved	-	-						
				 VERTIV™			Zeichnungs-Nr. / Drawing no.				Maßstab Scale	
							VP4N30AK				1:5	
Rev.	Change	Date	Name				Verwendet in / Used in				Blatt/Sheet	
							–				1/1	