

4

3

2

1

#10-32 BLIND PEM NUT
(REQUIRED FOR TOOLLESS MOUNTING)
3 PLACES

92.1
[3.63]

88.9
[3.50]

1555.8
[61.25]

76.2
[3.00]

1828.8
[72.00]

76.2
[3.00]

OUTPUT POWER

CIRCUIT	PHASE	RECEPTACLE TYPE (QUANTITY)	VOLTAGE (V)	MAX. CONTINUOUS AMPS (A)	
				PER RECEPTACLE	PER CIRCUIT
1	A	2xSDG400	277	16	16
2	B	2xSDG400	277	16	16
3	C	2xSDG400	277	16	16
4	A	2xSDG400	277	16	16
5	B	2xSDG400	277	16	16
6	C	2xSDG400	277	16	16
7	A	2xSDG400	277	16	16
8	B	2xSDG400	277	16	16
9	C	2xSDG400	277	16	16
10	A	2xSDG400	277	16	16
11	B	2xSDG400	277	16	16
12	C	2xSDG400	277	16	16

3P+N+E (IP67)



AGENCY COMPLIANCE:
ETL & c-ETL Listed to UL 62368-1
RoHS Compliant
FCC Part 15 Class A Conformance

ENVIRONMENTAL RATING:
Maximum Operating Temperature: 60C / 140F

NOTES
UNIT DIMENSIONS: 72in x 3in x 3in / 1829mm x 77mm x 77mm
SHIPPED WEIGHT: 31lbs (14.1kg)
SHIPPING DIMENSIONS: 72in x 9in x 7in / 1829mm x 223mm x 159mm
Toolless Mounting Hardware 61.25in / 1556mm and 64.75in / 1645mm

INPUT POWER

INPUT CORD	INPUT PLUG	WIRE COUNT	FREQUENCY (Hz)	VOLTAGE (V)	RATED AMPS (A)	MAX. CONT. AMPS (A)
10ft	3P+N+E (IP67)	3/N/PE	50/60	277/480V WYE	60A	48A

METERING PARAMETER	MEASUREMENT ACCURACY
VOLTAGE	±1%
CURRENT	±1% - Input Current ±1% - Circuit/Breaker Current

CORPORATE CAGE CODE 1EDC2		VERTIV 1777 YOLANDE AVENUE LINCOLN, NEBRASKA 68521		VP4NC0A0	VP4NC0A0-ASM										
		505 N. CLEVELAND AVE WESTERVILLE, OHIO 43082		PART NUMBER	DESCRIPTION										
<small>© 2025 VERTIV GROUP CORP. CONFIDENTIAL AND PROPRIETARY. ALL RIGHTS RESERVED. VERTIV AND THE VERTIV LOGO ARE TRADEMARKS OR REGISTERED TRADEMARKS OF VERTIV GROUP CORP. THIS DOCUMENT (AND THE INFORMATION IT CONTAINS) ARE THE PROPERTY OF VERTIV GROUP CORP. BY ACCEPTING IT INTO YOUR POSSESSION, YOU AGREE THAT YOU WILL KEEP THIS DOCUMENT AND ALL INFORMATION CONTAINED HEREIN IN STRICTEST CONFIDENCE AND WILL NOT COPY, RETRANSMIT USE (EXCEPT SOLELY FOR THE BENEFIT OF VERTIV GROUP CORP.), SELL, LEND, OR OTHERWISE DISPOSE OF SAME, DIRECTLY OR INDIRECTLY, WITHOUT THE EXPRESS WRITTEN PERMISSION OF VERTIV GROUP CORP., AND THIS DOCUMENT SHALL BE RETURNED TO VERTIV GROUP CORP. IMMEDIATELY UPON REQUEST.</small>															
MATERIAL: N/A		UNLESS OTHERWISE SPECIFIED TOLERANCE													
FINISH: N/A		<table border="1"> <tr> <th>MM (PRIMARY)</th> <th>INCHES (SECONDARY)</th> </tr> <tr> <td>X ±.25</td> <td>(X) ±.1</td> </tr> <tr> <td>XX ±.75</td> <td>(XX) ±.03</td> </tr> <tr> <td>XXX ±.25</td> <td>(XXX) ±.01</td> </tr> <tr> <td>HOLE DIA +.08</td> <td>HOLE DIA +.003</td> </tr> <tr> <td>ANGULAR</td> <td>±2°</td> </tr> </table>				MM (PRIMARY)	INCHES (SECONDARY)	X ±.25	(X) ±.1	XX ±.75	(XX) ±.03	XXX ±.25	(XXX) ±.01	HOLE DIA +.08	HOLE DIA +.003
MM (PRIMARY)	INCHES (SECONDARY)														
X ±.25	(X) ±.1														
XX ±.75	(XX) ±.03														
XXX ±.25	(XXX) ±.01														
HOLE DIA +.08	HOLE DIA +.003														
ANGULAR	±2°														
DESIGNED BY: JEFF MICEK	DATE: 2023-02-23	WEIGHT: -	CONTROL CHARACTERISTICS PART DESCRIPTION VP4NC0A0-ASM												
DRAWN BY: JEFF MICEK	DATE: 2026-02-23	SHEET: 1/1	THIRD ANGLE PROJECTION	SIZE B	SCALE 1:6 DOCUMENT NUMBER VP4NC0A0										

4

3

2

1