

AGENCY COMPLIANCE:
RoHS Compliant
FCC Part 15 Class A Conformance
UL & c-UL Listed 62368-1

NOTES


UNIT DIMENSIONS: 72in x 2in x 2.6in / 1829mm x 51mm x 66mm

DOGHOUSE: 1.4in / 36mm

SHIPPED WEIGHT: 22lbs (9.98kg)

Mounting Hardware: 7938 Vertical Mounting Bracket Kit; Toolless Mounting Hardware - Center to Center Spacing: 61.25in and 64.75in

INPUT POWER						
INPUT CORD	INPUT PLUG	WIRE COUNT	FREQUENCY (Hz)	VOLTAGE (V)	RATED AMPS (A)	MAX. CONT. AMPS (A)
10ft/3m	IEC60309 3P + N + E, 30A, Splashproof IP44	3/N/PE	50/60	200-240	30A	24A

 Dimensions in mm				Allgemeintoleranzen General tolerances		Oberfläche Finish		Werkstoff / Material		Gewicht: – Weight:	
				–		–		–			
				Drawn	Date 25/02/17	Name JM	Bezeichnung / Description rPDU, Switched Unit Level Monitoring EC, 30A, 240/415V WYE, 17.2KW, Vertical, (36) Combination C13/C19, 10ft/3m Power Cord.				
				Checked	–	–					
				Approved	–	–	Zeichnungs-Nr. / Drawing no. VP5N30AS Maßstab Scale 1:6				
				 VERTIV™							
–	–	–	–								
Rev.	Change	Date	Name				Verwendet in / Used in			Blatt/Sheet 1/1	