



Smoke Detector Kit Part Number: SD2



The SD2 is a low-voltage smoke detector with a built-in dry-contact relay output, suitable for use with any Geist environmental or power + environmental monitoring unit equipped with analog-sensor inputs. Comes pre-wired with a 12VDC power supply and a 25ft (7.6m) length, 2-conductor alarm wire for easy installation.

Specifications:

- Input Power: 100-240VAC, 2-3mA (avg.), 50/60Hz
- System Voltage: 12VDC
- Operating Temperature Range: 41°F to 135°F
- Operating Humidity Range: 0 to 95% RH non-condensing
- Sensor: Photoelectric Smoke Detector

Please note the information contained herein is for informational purposes only. Technical claims listed depend on a series of technical assumptions. Your experience with these products may differ if you operate the products in an environment, which is different from the technical assumptions. Geist reserves the right to modify these specifications without prior notice. Geist makes no warranties, express or implied, on the information contained in this document.

10008101

Geist Americas

800.432.3219
geistglobal.com

Geist DCiM
1.877.449.4150
geistglobal.com

Geist Europe

+44 (0) 1823 275100
geistglobal.com

Geist Asia

China
+86.755.86639505
geistglobal.com

Hong Kong
+852 90361927
geistglobal.com