## Environmental Monitor Product Overview

	Feature	Watchdog 15	Watchdog 100
On-Board Sensors	🔒 Temperature	•	•
On-Board Sensors	هُمْ Humidity / Dew point	•	•
External Sensor	# Plug-n-Play Sensor Ports	2	2
	Max Plug-n-Play Sensor Capacity	4	4
	# Dry-Contact / 0-5V Sensor Ports	0	4
Hardware	Built-in PoE	Optional	Optional
	Dry-Contact Relay Outputs	0	1
	Rackmount 19" 1U		•
	Ethernet	10/100	10/100
Web Server	USB		
	IPv6	•	•
	HTTP / HTTPS	•	•
3	DHCP	•	•
Firmware	JSON API	•	•
	Real Time Sensor Data Feeds	•	•
	Sensor Data Logging & Graphing	•	•
	Data Logs	CSV, JSON	CSV, JSON
	SNMP (v1, v2c, v3)	•	•
	Email & Email-to-SMS Alerts	•	•
	Alarm Escalations	•	•
	Alarm Repeat	•	•
	Alarm Delay	•	•
	Alarm Valid Hours	•	•
	Periodic Email Status Reports	•	•
	Encryption via TLS	•	•
	Login Security	3 Admin, Control, View Only	
	Compatible with Device Director	•	•
Benefits	FREE Firmware Updates	•	•
	FREE Technical Support	•	•
	Warranty	5 Years*	
Reg	Regulatory Compliance	UL, FCC, CE, RoHS	

Alert

adjustable

breached

via Email, Email-

call\*\* when user-


thresholds are

# Monitor

() Temperature ( Humidity/Dew Point Airflow **()** Door Position Smoke Water Leaks (7) Power Failure Battery

# Prevent

S Alert notifications Equipment Failure Downtime to-SMS, SNMP Traps, and voice (\$) Loss of Revenue **(a)** Loss of Reputation



#### Plug-n-Play Sensors: Temperature

Temperature/Humidity/Dew Point (GTHD) Temperature/Humidity/Dew Point (GT3HD) Temperature/Humidity/Dew Point/Airflow Analog-to-Digital Converter (A2D)

#### Analog/Dry Contact Sensors

Door Position (NO/NC) Smoke Detector (NO/NC) Flood Sensor (Conductivity) Water Sensing Cable Kit (NO/NC) Power Failure Sensor (0-5V) Current Transducer 30/60/120A (0-5V) Isolated Coltage Sensor (0-5V)

#### Accessories

GEIST MONITOR

5-Port Splitter -48 VDC Power Supply PSTN Auto-Dialer (Analog) GSM AUto-Dialer (SIM card required)

#### Ideally suited for: Data Centers Telecom

Edge Applications Network Closets

Retail Data Closets



\*Standard 3 year warranty incresed to 5 years with product warranty registration within 120 days of purchase \*\*Relay-controlled auto dialer required

### geistglobal.com

**Geist Americas** 

Geist Europe

# Geist Asia





#### \*Relay-controlled auto dialer required

#### Variety of Environmental Monitors Available

Geist environment monitors are used for a wide range of other applications including traffic control boxes, climate-controlled storage, wine cellars, air-traffic control communications closets, research laboratories, stability chambers, greenhouses, livestock, poultry farms and museums. Our products are fully scalable to meet various special needs.

# Free Tech Support Free Firmware Updates No Annual Fees



#### geistglobal.com

Geist Americas

Geist Europe

0 432 3219

11 (N) 1823 275100

Geist Asia China +86.755.86639505

## Health Care



Monitor and validate temperature among various environments within healthcare facilities including hospitals, blood and tissue banks, laboratories and more. Our sensors are designed to monitor extreme temperatures and allow users to satisfy FDA 21 CFR Part 11 compliant reporting.

## Cold Storage



Our environment monitors enable users to strategically monitor cold-storage facilities among restaurants, cafeterias, grocery stores and warehouses across the globe to protect perishable inventory ensuring food quality and safety.

#### 30010605